



CONTAINMENT

C o r p o r a t i o n

800-235-7421

www.ContainmentCorp.com

HEAVY DUTY "RAMP" OPTIONS FOR FUEL TANKERS

HEAVY DUTY RAMPS ... Each heavy duty epoxy coated steel ramp is welded steel fabrication consisting of 3/8" thick steel web supporting frame and 3/8" thick steel diamond plate surface. Maximum load bearing, 36,000 lbs. per axle (H-20 loading).



X

Part Number: CST-XR00

One piece ramp. Crowns over end wall and indexes around panel center joint.

Includes integral retainers for Line-of-Sight poles.

"X" Ramp – Dim. 12'W x 5'L (2.5' inside/ 2.5' outside); Peaks at 9.5"H. Wt. 2,200 lbs.



XX

Part Number: CST-XXR0

Two piece ramp. Bolts together over end wall. Inside section indexes around panel center joint.

Includes integral retainers for Line-of-Sight poles. Shown with optional "Corner guards" (only employed with Standard CAMEL).

"XX" Ramp – Dim. 12'W x 10'L (5' inside/ 5' outside); Peaks at 9.5"H. Wt. 2,700 lbs.



XXX

Part Number: CST-XXXR

Two piece ramp. Bolts together at end wall.

Inside section indexes around panel center joint. Includes integral retainers for Line-of-Sight poles.

"XXX" Ramp – Dim. 12'W x 16'L (8' inside/ 8' outside); Peaks at 9.5"H. Wt. 3,300 lbs.